IMPORTANT NOTICE: The current, official version of this document is available on the Sandia National Laboratories WIPP Online Documents web site. A printed copy of this document may not be the version currently in effect.

ACTIVITY/PROJECT SPECIFIC PROCEDURE

SP 9-11
CALCULATION OF DENSITIES FOR GROUNDWATER IN WIPP WELLS
Revision 3

Effective Date: December 10, 2015

Author:	Patricia B. Johnson	*Original signed by P.B. Johnson*	*12/9/2015*
	(printed name)	(signature)	(date)

1.0 Purpose and Scope

This procedure prescribes the Sandia National Laboratories (SNL), Waste Isolation Pilot Plant (WIPP) process for the calculation of densities for groundwater in WIPP wells. The objective of this procedure is to describe how groundwater densities in the WIPP wells are calculated. The densities are used to satisfy permit requirements which typically include the calculation of freshwater heads.

This Specific Procedure (SP) is intended to direct SNL technical personnel in the actions needed to obtain high-quality data that meet SNL Quality Assurance (QA) standards. All future calculated density outputs will be documented in memorandums to file that will reference this SP. This SP is governed by Nuclear Waste Management Procedure (NP) 9-1, Analyses, which directs analyses documented in routine calculations.

Acronyms and definitions for terms used in this procedure may be found in the Glossary located on the Sandia National Laboratories (SNL) WIPP Online Documents web site.

2.0 Implementation Actions

2.1 Safety

The activities described in this SP shall conform to SNL Environmental Safety and Health programs (ES&H). All activities described in this SP will be conducted in the SNL office facility.

2.2 Responsibilities

The Technical Staff are responsible for performing the calculations outlined in this procedure, documenting all required information described in this SP, and assuring the latest revision of this document is followed.

If the procedure cannot be worked as written, the user has the responsibility to stop work and resolve all concerns with the PI and/or QA, as appropriate, prior to proceeding with the work.

© 2015 Sandia Corporation

2.2 Equipment

The equipment will be limited to a computer and its associated operating system. This will include a spreadsheet program, typically Excel.

2.3 Procedure for Calculating Densities

The densities of the water in the WIPP wells shall be calculated using pressure (head and barometric where applicable) data collected by pressure transducer gauges (PTs), the depths of the PTs, and the corresponding depth to water data. Specifically, the measured pressure values shall be divided by the PT depth minus the closest corresponding depth to water (from or adjusted to the same measurement point elevation), and that result will then be divided by 0.4335 (pressure to feet of water conversion), as depicted in the following equation:

$$PD = \left[\frac{P_{meas} * P_f}{Z_1 - DTW} \right] / C$$

Where,
PD = Pressure Density (grams per centimeter cubed (g/cm^3)
P_{meas*} = the measured pressure head (psia or psig)
P_f = density of freshwater (1.000 g/cm^3)
Z_1 = installation depth of the PT (ft below reference point)
DTW = depth to water (ft below reference point)
C = conversion coefficient (0.4335 psi/ft, for fresh water)
Note: P_{meas*} is equal to P_{meas} for gauge (vented) sensors or P_{meas} minus barometric pressure (BP, psia) for absolute (non-vented) sensors.

When using absolute pressure data, the closest corresponding barometric pressure values shall be subtracted from the water pressures prior to dividing by the PT depth minus the depth to water, then the results will be divided by 0.4335. This calculation results in a density value for the date and time of the subject depth to water and the closest corresponding pressure data. Depending on data availability, densities are calculated and averaged for a final value. Ideally, attempts are made to use a consistent time period for all the wells. If available, at least four consecutive density estimates (as given by the equation above) are averaged to create a representative value. The densities are used for the purposes of calculating equivalent freshwater heads for WIPP wells and for fulfilling regulatory permit requirements.

As part of the documentation process, sources and background information are provided for the data. This information will be included with future records submittals in memorandum format, and will typically consist of the following:

- Monitor Well Name
- Prior Year Average Calculated Density
- Number of Densities Averaged
- PT and Cable Type (to indicate absolute or gauge pressure values)
- Time Period of Data
- PT File Name(s)
- PT Installation Depth - in feet (ft) below reference point (i.e., below top of casing (BTOC), below top of tubing (BTOT))

- Ideal Installation Depth for the PT (ft below reference point) – mid-formation (ideally, all PTs are installed at or as close to mid-formation depth as possible)
- Date of PT Installation
- PT Installation Documentation Reference – logbook page
- Hard copy or reference to depth to water data

2.4 Data Sources

Two standard components of the calculated densities are the depth to water data and PT depths. The SNL depth to water data and PT installation data are located in the Records Center in the following data packages:

- Long-Term Monitoring Notebooks (package ERMS 543277), and
- WIPP Site Well Testing Notebooks (package ERMS 540244).

The depth to water data from the Operations and Maintenance (O&M) contractor, currently Regulatory and Environmental Services (RES), are located in the Records Center in the following data package:

- WRES Depth to Water Data, submitted to SNL in monthly memoranda (package ERMS 525178)

All additional data sources will be provided in the memorandum submitted to the Records Center.

3.0 Records

The following records, generated through implementation of this procedure, shall be prepared and submitted to the WIPP Records Center in accordance with NP 17-1, “Records”:

QA Record

- Memorandum containing density output data and associated data references

4.0 Appendices

There are no appendices associated with this SP.

This work of authorship was prepared as an account of work sponsored by an agency of the United States Government. Accordingly, the United States Government retains a nonexclusive, royalty-free license to publish or reproduce the published form of this contribution, or allow others to do so for United States Government purposes. Neither Sandia Corporation, the United States Government, nor any agency thereof, nor any of their employees makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately-owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by Sandia Corporation, the United States Government, or any agency thereof. The views and opinions expressed herein do not necessarily state or reflect those of Sandia Corporation, the United States Government or any agency thereof.

Sandia National Laboratories is a multi-program laboratory managed and operated by Sandia Corporation, a wholly owned subsidiary of Lockheed Martin Corporation, for the U.S. Department of Energy’s National Nuclear Security Administration under contract DE-AC04-94AL85000.

Parties are allowed to download copies at no cost for internal use within your organization only provided that any copies made are true and accurate. Copies must include a statement acknowledging Sandia Corporation's authorship of the subject matter.